



This MotoCAP safety rating applies to:

Harley Davidson **Brand:** Model: Lea Wtchscrn Type: Glove - Leather Date purchased: 24 March 2020 Sizes tested: M, L and XL Test glove gender: **Female** Style: Cruiser RRP: \$149.95

Test Results Summary:

	Rating	Score
MotoCAP Protection Rating	**	3.1
Abrasion	10/10	5.96
Seam strength	1/10	2.7
Impact	1/10	0.0
Water resistance	2/10	11.5

These gloves are fitted with impact protection for the palms only. There is no impact protection for the knuckles. There is no provision for ventilation to allow airflow movement through the glove. This glove has limited range of fastening for wrist retention as it is fastened by a press stud and zip.

Gloves - Crash Impact Risk Zones

High risk of impact

High risk of abrasion

This diagram is a pictorial representation of the crash impact risk Zones.



High risk of abrasion

Medium risk of abrasion



Abrasion Resistance

The gloves were tested for abrasion resistance in accordance with MotoCAP test protocols. The diagram below is a visual indication of the likely abrasion performance of the materials in each Zone calculated from the data in the table below. The colour coding is based on the worst performing material in each zone.



Abrasion Resistance Performance

Abrasion rating 10/10 Abrasion score 5.96

Determining Criteria	Area	Good	Acceptable	Marginal	Poor
High abrasion risk	Zone 1 & 2	> 4.0	2.7 - 4.0	1.2 - 2.6	< 1.2
Medium abrasion risk	Zone 3	2.5	1.8 - 2.5	0.8 - 1.7	< 0.8

Individual Abrasion Resistance Results: - The table below shows the test results for time to abrade through all layers of the materials. Calculated for each sample by Zone, type and area coverage of each material as a proportion of that Zone. Abrasion times are capped at a maximum of 10.00s.

Abrasion time for each test (seconds)

	•	,							
Zones 1	Coverage (%)	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5	Sample 6	Average	
Material A	100%	4.72	7.27	5.29	5.51	5.60	7.36	5.96	G
Zone 2	Coverage (%)	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5	Sample 6	Average	
Material A	100%	4.72	7.27	5.29	5.51	5.60	7.36	5.96	G
Zone 3	Coverage (%)	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5	Sample 6	Average	
Material A	100%	4.72	7.27	5.29	5.51	5.60	7.36	5.96	G

Details of materials used in glove - derived from manufacturer provided information

Material A Leather shell, water resistant layer, foam layer and fabric inner liner



Seam Tensile Strength

The tensile strength of the gloves seams and glove restraint (the force required to drag off a properly fastened glove) were tested in accordance with MotoCAP test protocols. The diagram below illustrates the tensile strength and wrist restraint results in terms of the likely performance of the glove in a crash and is a pictorial representation of the data from the tables below.



Seam Strength Performance

Seam strength rating	1/10
Seam strength score	2.7

Determining Criteria	Unit	Good	Acceptable	Marginal	Poor
Seam tensile strength	(N/mm)	> 11	9 - 11	6 - 8.9	< 6
Glove restraint	(N)	> 200	100 - 200	50 - 99	<50

Individual Seam Strength Results: - The table below shows the seam tensile strength in newtons per millimeter (N/mm) for each seam tested by Zone and the average result for each Zone.

Seam tensile strength (N/mm)

Area	1	2	3	4	5	Average
Zones 1 & 2	12.76	8.24	11.54	12.62	3.90	9.81 A
Zone 3	11.36	16.96	11.13	6.18	11.55	11.44 G

Individual Glove Restraint Results: - The table below shows the force required to remove the restrained glove in newtons (N) for each of the five gloves tested and the average result.

Glove restraint (N)

Glove	1	2	3	4	5	Average
Wrist restraint	60.8	49.5	49.3	49.1	44.8	50.7 M



Impact Protection

The glove was tested for impact protection and coverage In accordance with MotoCAP test protocols. The diagram below is a visual indication of the likely performance of each impact protector calculated from the data in the table below. The colour coding is based on the worst performing score for average or maximum force for each impact zone. Areas shaded black are not considered in the impact protection ratings.



^{*} Poor may also indicate that no impact protector is present in the glove

Impact Protector Results: - The table below shows the test results for each strike on each impact protector in kilonewtons (kN) and their area of coverage in percentage (%) within the Zone. Impact forces are capped at a maximum of 10.0kN.

Impact protector type	Knuckles	Palm		
Average force (kN)	Р	9.8 P		
Maximum force (kN)	Р	10.0 P		
Coverage of zone 1 area	0%	40%		

Individual test results: - The table below shows the test results for each strike on each impact protector in kilonewtons (kN) and the position of the strike. Impact forces are capped at a maximum of 10.0kN.

Impact protector type	Knuckles	No impact prot	ector present	Palm	
Strike number	1	2	3	1	2
Impact Protector 1				10.0	9.6
Impact Protector 2				10.0	9.2
Impact Protector 3				10.0	9.7



Water spray and rain resistance

This glove is advertised as water-resistant, and so has been tested for water spray and rain resistance according to the MotoCAP test protocols. The table below shows the water absorbed (ml) and the wetting proportion (%) of the glove and under-glove due to water absorption.

	Water absorbe	ed by glove	Water absorbed by cotton glove			
	Volume (ml)	Percentage (%)	Volume (ml)	Percentage (%)		
Pair 1	23.8	14%	23.0	112%		
Average	23.8	14%	23.0	112%		

Location of wetting:

Visible wetting to the cotton under-glove was present at the palm and the top of the hand in both gloves tested.

Assessment Details.

Brand Harley Davidson
Model Lea Wtchscrn
Type Glove - Leather
Date purchased 24 March 2020

Tested by AMCAF, Deakin University Report approved by MotoCAP Chief Scientist

Garment test reference G19L46
Rating first published January 2021
Rating updated 13 August 2021