



This MotoCAP safety rating applies to:

Brand 4SR

Model Cool Evo Brown
Type Jacket - Leather
Date purchased 20 February 2023

Sizes tested 56 and 58
Test garment gender Male
Style Sports
RRP \$499.00

Test Results Summary	Rating	Score
MotoCAP Protection Rating	***	47.7
Abrasion	4/10	3.34
Burst	10/10	1225
Impact	8/10	62.6
MotoCAP Breathability Rating	+	0.119
Moisture Vapour Resistance	-	123.4
Thermal Resistance	-	0.245
Water resistance	N/A	N/A

This garment is fitted with impact protectors for the elbows and shoulders. A pocket is provided for an aftermarket back protector. Perforated leather is located under arms and sides to allow airflow movement through the garment.

Jacket and Pants - Crash Impact Risk Zones

This diagram is a pictorial representation of the crash impact risk Zones.

		Removable Thermal liner Water-resista Removable Elbow Shoulder Back	
Zone 1	Zone 2	Zone 3	Zone 4
High risk of abrasion	High risk of abrasion	Medium risk of abrasion	Low risk of abrasion
High risk of impact	-		



Abrasion Resistance

The jacket was tested for abrasion resistance in accordance with MotoCAP test protocols. The diagram below is a visual indication of the likely abrasion performance of the materials in each zone calculated from the data in the table below. The colour coding is based on the worst performing material in each zone.



Abrasion Resistance Performance

Abrasion rating	4/10
Abrasion score	3.34

Determining Criteria	Area	Good	Acceptable	Marginal	Poor
High abrasion risk	Zones 1 & 2	> 5.6	3.0 - 5.6	1.3 - 2.9	< 1.3
Medium abrasion risk	Zone 3	> 2.5	1.8 - 2.5	0.8 - 1.7	< 0.8
Low abrasion risk	Zone 4	>1.5	1.0 - 1.5	0.4 - 0.9	< 0.4

Individual Abrasion Resistance Results: - The table below shows the test results for time to abrade through all layers of the materials. Calculated for each sample by Zone, type and area coverage of each material as a proportion of that Zone. Abrasion times are capped at a maximum of 10.00s.

Abrasion time for each test (seconds)

Zones 1 & 2	Coverage (%)	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5	Sample 6	Average	
Material A	35%	10.00	5.70	5.60	10.00			7.82	G
Material B	65%	2.87	2.55	4.38	2.69	2.88	3.49	3.14	Α
Zone 3	Coverage (%)	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5	Sample 6	Average	
Material B	90%	2.87	2.55	4.38	2.69	2.88	3.49	3.14	G
Material C	10%	3.20	3.15	2.96	2.72	2.62	3.27	2.99	G
Zone 4	Coverage (%)	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5	Sample 6	Average	
Material B	100%	2.87	2.55	4.38	2.69	2.88	3.49	3.14	G

Details of materials used in jacket

Material A	Quilted leather shell with mesh inner liner
Material B	Leather shell with mesh inner liner
Material C	Perforated leather shell with mesh inner liner



Burst Strength

The jacket was tested for burst strength in accordance with MotoCAP test protocols. The diagram below illustrates the burst strength results in terms of the likely performance of the garment in an impact and is a pictorial representation of the data from the table below.



Burst rating	10/10
Burst score	1225

Determining Criteria	Unit	Good	Acceptable	Marginal	Poor
Burst strength	(kPa)	> 1000	800 - 1000	500 - 799	< 500

Individual Burst Strength Results: - The table below shows the burst pressure in kilopascals (kPA) for each sample tested by Zone and the average result for each zone.

Burst pressure for each seam (kPA)

Area	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5	Sample 6	Average	
Zones 1 & 2	1425	1078	1517	896	1271	1366	1259	G
Zones 3 & 4	1132	644	571	1475	1700	1020	1090	G



Impact Protection

The jacket was tested for impact protection and coverage in accordance with MotoCAP test protocols. The diagram below is a visual indication of the likely performance of each impact protector calculated from the data in the table below. The colour coding is based on the worst performing score for average or maximum force for each impact zone. Areas shaded black are not considered for impact protection ratings.



Impact Protection Performance

Impact rating	8/10
Impact score	62.6

Determining Criteria	Unit	Good	Acceptable	Marginal	Poor*
Impact force	(kN)	< 15	15 - 24	25 - 30	> 30

^{*} Poor may also indicate that no impact protector, or impact protector pocket is present in the garment

Impact Protector Results: - The table below shows the average and maximum force transmitted through each impact protector type in kilonewtons (kN) and their area of coverage as a proportion (%) of the Zone.

Impact protector type	Elbow		Shoulder
Average force (kN)	14.7	G	11.8 G
Maximum force (kN)	19.6	Α	15.2 A
Coverage of Zone 1 area	130%	<u> </u>	110%
Coverage of Zone after displacement	100%		100%

Individual Impact Protector Results: - The table below shows the test results for each strike on individual impact protectors in kilonewtons (kN) and the position of the strike. Individual strike results are capped at a maximum of 50kN.

Force transfer for each impact strike (kN)

Impact protector type	Elbow	Elbow Shoulder				
Strike location	Centre	Mid	Edge	Centre	Mid	Edge
Impact Protector 1	11.8	16.4	13.3	10.8	12.4	13.2
Impact Protector 2	11.8	13.7	18.6	10.4	10.9	13.2
Impact Protector 3	11.9	15.3	19.6	10.2	10.2	15.2



Breathability

The jacket was tested for breathability following the MotoCAP test protocols. The table below shows the moisture vapour resistance and the thermal resistance values obtained.

Without removable liners		With water-resistant liner			
Breathability rating		Breathability rating		N/A	
Breathability score	0.119	Breathability score		N/A	
Moisture Vapour Resistance - R _{et} (kPa.m²/W)		1	2	Average	
Without removable liner	S	122.5	124.3	123.4	
With water-resistant line	er	N/A	N/A	N/A	
Thermal Resistance - R _{ct} (K.m²/W)		1	2	Average	
Without removable liner	S	0.238	0.253	0.245	
With water-resistant line	er	N/A	N/A	N/A	

Water spray and rain resistance

This jacket has not been advertised as water-resistant so has not been tested for water spray and rain resistance.

Assessment Details.

Brand 4SR

Model Cool Evo Brown
Type Jacket - Leather
Date purchased 20 February 2023

Tested by AMCAF, Deakin University Report approved by MotoCAP Chief Scientist

Garment test reference J23L02
Rating first published March 2023
Rating updated 20 March 2023