

мотосар

This MotoCAP safety rating applies to:

Brand:	Rev'it
Model:	Redhill
Туре:	Glove - Leather
Date purchased:	29 June 2023
Sizes tested:	L, XL and 2XL
Test glove gender:	Male
Style:	All Purpose
RRP:	\$159.01

Test Results Summary:

	Rating	Score
MotoCAP Protection Rating	***	3.2
Abrasion	8/10	4.08
Seam strength	6/10	9.4
Impact	4/10	7.9
Water resistance	N/A	N/A

This glove is fitted with impact protectors for the knuckles and palm areas. Perforated leather on the side of the fingers provide continuous airflow within the glove.

Gloves - Crash Impact Risk Zones


This diagram is a pictorial representation of the crash impact risk Zones.





Abrasion Resistance

The gloves were tested for abrasion resistance in accordance with MotoCAP test protocols. The diagram below is a visual indication of the likely abrasion performance of the materials in each Zone calculated from the data in the table below. The colour coding is based on the worst performing material in each zone.



riigh abraoion noix			2		=
Medium abrasion risk	Zone 3	2.5	1.8 - 2.5	0.8 - 1.7	< 0.8

Individual Abrasion Resistance Results: - The table below shows the test results for time to abrade through all layers of the materials. Calculated for each sample by Zone, type and area coverage of each material as a proportion of that Zone. Abrasion times are capped at a maximum of 10.00s.

Zones 1	Coverage (%)	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5	Sample 6	Average	
Material A	40%	10.00	10.00	10.00	10.00	10.00	10.00	10.00 (G
Material B	60%	3.62	2.92	1.90	2.51	1.67	3.01	2.60	М
Zone 2	Coverage (%)	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5	Sample 6	Average	
Material C	6%	1.54	3.82	4.38	3.06	5.09	6.51	4.07 (G
Material B	94%	3.62	2.92	1.90	2.51	1.67	3.01	2.60	М
Zone 3	Coverage (%)	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5	Sample 6	Average	
Material D	12%	8.69	5.69	6.72	8.98			7.52 (G
Material B	88%	3.62	2.92	1.90	2.51	1.67	3.01	2.60	G

Abrasion time for each test (seconds)

Details of materials used in glove - derived from manufacturer provided information

- Material ALeather shell over hard-shell armourMaterial BLeather shell with mesh inner linerMaterial CSuede patch over leather shell with mesh inner liner
- Material D Leather shell, foam layer, mash layer and mesh inner liner



Seam Tensile Strength

The tensile strength of the gloves seams and glove restraint (the force required to drag off a properly fastened glove) were tested in accordance with MotoCAP test protocols. The diagram below illustrates the tensile strength and wrist restraint results in terms of the likely performance of the glove in a crash and is a pictorial representation of the data from the tables below.



Determining Criteria	Unit	Good	Acceptable	Marginal	Poor
Seam tensile strength	(N/mm)	> 11	9 - 11	6 - 8.9	< 6
Glove restraint	(N)	> 200	100 - 200	50 - 99	<50

Individual Seam Strength Results: - The table below shows the seam tensile strength in newtons per millimeter (N/mm) for each seam tested by Zone and the average result for each Zone.

Seam tensile strength (N/mm)

Area	1	2	3	4	5	Average
Zones 1 & 2	16.50	9.72	11.51	5.60	7.03	10.07 A
Zone 3	9.64	4.08	5.69	7.67	15.21	8.46 M

Individual Glove Restraint Results: - The table below shows the force required to remove the restrained glove in newtons (N) for each of the five gloves tested and the average result.

Glove restraint (N)

Glove	1	2	3	4	5	Average
Wrist restraint	240.5	210.2	138.7	238.0	225.7	210.6 G



Impact Protection

The glove was tested for impact protection and coverage In accordance with MotoCAP test protocols. The diagram below is a visual indication of the likely performance of each impact protector calculated from the data in the table below. The colour coding is based on the worst performing score for average or maximum force for each impact zone. Areas shaded black are not considered in the impact protection ratings.



* Poor may also indicate that no impact protector is present in the glove

Impact Protector Results: - The table below shows the test results for each strike on each impact protector in kilonewtons (kN) and their area of coverage in percentage (%) within the Zone. Impact forces are capped at a maximum of 10.0kN.

Impact protector type	Knuckles	Palm		
Average force (kN)	1.5 G	4.7 A		
Maximum force (kN)	1.9 G	5.9 M		
Coverage of zone 1 area	100%	15%		

Individual test results: - The table below shows the test results for each strike on each impact protector in kilonewtons (kN) and the position of the strike. Impact forces are capped at a maximum of 10.0kN.

Impact protector type	Knuckles			Palm	
Strike number	1	2	3	1	2
Impact Protector 1	1.4	1.2	1.5	5.3	4.1
Impact Protector 2	1.5	1.1	1.9	5.9	5.3
Impact Protector 3	1.7	1.3	1.7	3.4	4.5



Water spray and rain resistance

This glove has not been advertised as water resistant so has not been tested for water spray and rain resistance.

Assessment Details.

Brand Model Type Date purchased Tested by Report approved by Garment test reference Rating first published Rating updated Rev'it Redhill Glove - Leather 29 June 2023 AMCAF, Deakin University MotoCAP Chief Scientist G23L37 August 2023 23 August 2023